

## STAINLESS STEEL STRINGER





## **PERFORMANCE**

- ALL STAINLESS
  STEEL STRINGER WITH
  WASHDOWN
  CONSTRUCTION AND
  FDA APPROVED FOOD
  GRADE TUBING
  FOR MAX. SANITATION
- SPEEDS UP TO 250 CYCLES PER MINUTE. AVAIL. IN HEAVY DUTY CONSTRUCTION FOR HIGHER SPEEDS
- ELECTRICS ARE
  120V/230V SINGLE
  PHASE STANDARD AND
  240V/480V THREE
  PHASE AVAIL. WITH
  HEAVY DUTY




## **DESIGNS**

- STANDARD ECONO OPTION GIVES USER ABILITY TO CREATE ZIG-ZAG PATTERNS
- SINGLE LOOP ATTACHMENT ALLOWS USERS TO CREATE CIRCLES, SLANTED ZIG-ZAGS AND ZIG-ZAGS PATTERNS
- DOUBLE LOOP ATTACHMENT ALLOWS USERS TO CREATE FIGURE-8 AND CROSS-HATCHING DESIGNS AS WELL AS ALL ABOVE PATERNS



TECHNOLOGY

- WOODY'S PATENTED
  MOTOR DRIVEN
  STRAINER FILTERS
  DECORATING MATERIAL
  TO PREVENT CLOGS IN
  NOZZLE TUBE OUTLETS
- PLC TOUCH-SCREEN CONTROLS STANDARD WHEN SELF-PURGING NOZZLE TUBE IS ORDERED
- AVAILABLE WITH A STANDARD STROKE OF 2" OR WITH A LONG STROKE TO DECORATE UP TO 4" WIDE



## **UPGRADES**

- THE SELF-PURGING
  NOZZLE TUBE CLEARS
  SOFT CONTAMINATION
  SUCH AS CRUMBS OR A
  BUILD UP OF
  DECORATING
  MATERIAL FROM THE
  OUTLETS
  AUTOMATICALLY
- THE NOZZLE HEATER
  KEEPS THE NOZZLE
  TUBE WARM TO
  ENSURE AN EVEN
  FLOW OF DECORATING
  MATERIAL; ALSO
  AVAILABLE AS A
  HEATED ENCLOSURE